



NIK SARANG
INDUSTRIAL COATINGS

PRODUCT DATASHEET

INSTANT THINNER 10000

NIKTHIN 10000- T400

Dec 2025

www.niksarang.com



NIK SARANG
INDUSTRIAL COATINGS

INSTANT THINNER 10000

NIKTHIN 10000- T400

Product

Description:

Recommended Use:

Certificate /

Approval:

Technical Data:

NIKTHIN 10000-T400 is a clear, water-like liquid that mixture of properly selected non-reactive organic solvents for thinning a wide range of Paint.

To reduce and adjusting the flow of paints for different types of application methods to Improves the spray characteristics. Can also be used as cleaner for pumps and tools before and after painting.

In compliance with ISO 12944-5, BS 9453

Color Colorless to Light Yellow

Solid by volume 0%

Specific Gravity **0.82±0.03 gr/cm3**

Flash point **27 °c**

Shelf life **24 months at 25° C**

Depending on storage conditions, mechanical stirring may be necessary before usage. If the shelf life is exceeded, please contact NIK SARANG for further advice.

Package Bulk containers, 1000 liter containers, 200 liter containers, 20 liter containers, 4 liter containers, 1 liter containers.

Storage:

The product should be kept in securely closed containers during transport and storage. Exposure to air and extremes of temperature should be avoided.

For the full shelf life of polyurethane Spraying Thinner to be realized ensure that between use the container is firmly closed and the temperature is between 5°C/41°F and 35°C/95°F. Keep out of direct sunlight.

Safety:

Handle with care. Before and during use, observe all safety labels on packaging and paint containers, consult Nik Sarang Material Safety Data Sheets and follow all local or national safety regulations. Avoid inhalation, avoid contact with skin and eyes, and do not swallow. Take precautions against possible risks of fire or explosions as well as protection of the environment. Use only in well - ventilated areas.

Caution:

Flammable. Harmful by inhalation and in contact with skin. Risk of serious damage to eyes. Irritating to respiratory system and skin.



NIK SARANG
INDUSTRIAL COATINGS

INSTANT THINNER 10000
NIKTHIN 10000- T400

**General
Information:**

In all cases of doubt, or when symptoms persist, seek medical attention.
Never give anything by mouth to an unconscious person. Show this label or product container to the medically authorized person.

Inhalation:

Move into fresh air and keep at rest. Perform artificial respiration if breathing has stopped. For breathing difficulties oxygen may be necessary. Get medical attention.

Ingestion

Do not induce vomiting. If vomiting occurs, the head should be kept low so that stomach vomit doesn't enter the lungs. Get medical attention immediately!

Skin Contact:

Remove contaminated clothing immediately and wash skin with soap and water. Continue to rinse for at least 15 minutes.

Eye Contact:

Immediately flush with plenty of water for up to 15 minutes. Remove any contact lenses and open eyelids widely. If irritation persists: Seek medical attention and bring along these instructions.

**Extinguishing
Media:**

Extinguish with foam, carbon dioxide or dry powder.

**Special Fire
Fighting
Procedures:**

Avoid breathing fire vapors.

**Unusual Fire &
Explosion
Hazards:**

Toxic, irritating or flammable fumes from reaction with water or steam

**Protective
Measures in Fire:**

Wear full protective clothing. Use air-supplied respirator during firefighting.



NIK SARANG
INDUSTRIAL COATINGS

INSTANT THINNER 10000
NIKTHIN 10000- T400

Safety: Handle with care. Before and during use, observe all safety labels on packaging and paint containers. Avoid inhalation, avoid contact with skin and eyes, and do not swallow. Take precautions against possible risks of fire or explosions as well as protection of the environment

The information and recommendations set forth in this Product Data Sheet are based upon tests conducted by or on behalf of The NIK SARANG Company. Such information and recommendations set forth herein are subject to change and pertain to the product offered at the time of publication. Consult your NIK SARANG representative to obtain the most recent Product Data Information and Application Bulletin. The NIK SARANG Company warrants our products to be free of manufacturing defects in accord with applicable NK SARANG quality control procedures